



PRODUCT DATA SHEET

Havens Coolant Universal Antifreeze Coolant G11 33%-50%

DESCRIPTION

Havens Coolant Universal Antifreeze Coolant G11 33%-50% pre-mixed ready for use. Ethylene glycol based. For use in all makes and models of cars, both automotive engines and heavy-duty diesel engines. It's designed to protect the cooling systems of water-cooled petrol engines.

PROPERTIES

- Ready for use
- Efficient protection down to -36°C during winter condition
- Does not foam or clog radiators

APPLICATIONS

The majority of passenger cars' and light diesel vehicles' radiators can use Havens Coolant. Havens Coolant is a full mono ethylene glycol-based coolant for a liquid cooled crankcase system. It contains anti-corrosion and anti-rust additives. It is harmless to rubber and does not foam or clog radiators.

PERFORMANCE LEVELS

Meets and exceeds:

ASTM D 3306; ASTM D 4656; ASTM D 4985; ASTM D 5345; SAE J814C; SAE J1038; SAE J1941; SAE J1034; GM 1899M; GM 6043M; GM 1825M; Ford ESE-M97B44-A; Ford ESE-M97B18-C; Chrysler MS-7170; Freightliner 48-22880; Cummins 90T8-4; Waukesha 4-19470; White (GMC Div. Of Volvo); John Deere 8650-5; Case Corp. MS1710; Navistar B1 (B6-008GO); Cummins 3666132; Detroit Diesel 7SE298; Ford New Holland 9-86; John Deere H-5; Mack Truck 014GS17004; ATA RP 302A; G11.

TYPICAL PROPERTIES

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	HAVENS COOLANT	
Viscosity Grade			50%	33%
Density @ 15°C	ASTM D1122	kg/l	1.060	1.050
Boiling point	ASTM D1120	°C	107	110
Freezing point	ASTM D1177	°C	-36	-17

The values shown above are typical values at the date of publication. Havens Lubricants reserves the right to change these typical values without prior notice.

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.havenslubricants.com.