



PRODUCT DATA SHEET

Havens GEO SAE 15W40

DESCRIPTION

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engine applications.

PROPERTIES

This lubricant assures:

- Alternative fuel performance:
- Great performance for medium and heavy-duty vehicles using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control; and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

APPLICATIONS

Wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engines.

TYPICAL PROPERTIES

Havens GEO SAE 15W40			
Typical Properties	SAE Grade		15W40
	API level		CI-4/SL
Test Parameters	ASTM Method		Typical Values
Density @ 15°C, kg/l	ASTM D1298		0.87
Viscosity @ 100°C, cSt	ASTM D445		15.8
Viscosity @ 40°C, cSt	ASTM D445		126
Viscosity Index	ASTM D2270		132
Flash Point, °C	ASTM D92		230
BN, mg KOH/g	ASTM D2896		6
Pour Point, °C	ASTM D97		-27

October 2017

The values shown above are typical values at the date of publication. Havens Lubricants reserves the right to change these typical values without prior notice.