



PRODUCT DATA SHEET

Havens ATF VI

DESCRIPTION

Havens ATF-VI is a high performance, fully synthetic automatic transmission fluid that meets or exceeds the stringent requirements of DEXRON-VI specification and provides warranty protection for 2006 and newer General Motor's vehicles. It also provides improved performance in older vehicles, wherever DEXRON is specified.

PROPERTIES

- Extended fluid life
- Improved oxidation and thermal stability
- Outstanding resistance against sludge and deposit formation
- Improved anti-wear protection which contributes to extended transmission life
- Outstanding low temperature performance

APPLICATIONS

For most 2006 and newer GM vehicles.

PERFORMANCE LEVEL

Meets and exceeds:

- General Motor's DEXRON-VI

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	HAVENS ATF VI
Density @ 15°C	ASTM D1298	kg/l	0.84-0.87
Color	ASTM D1500	-	Red
Viscosity @ 100°C	ASTM D445	cSt	5.83
Viscosity @ 40°C	ASTM D445	cSt	29.5
Viscosity Index	ASTM D2270	-	Min 145
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-50
Fire Point	ASTM D92	°C	Min 185
Brookfield viscosity @-40 °C	ASTM D2983	cP	11,500
Copper Strip Corrosion	ASTM D130	-	1b
Foaming	ASTM D892	-	0/0/0

The values shown above are typical values at the date of publication. Havens Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.havenslubricants.com.