



PRODUCT DATA SHEET

Havens Chainsaw Oil 100

DESCRIPTION

Havens Chainsaw Oil 100 is a mineral-based high-performance oil for once-through loss lubrication. Thanks to the outstanding adhesion properties and first-class lubricating effect, provides optimum protection of moving parts such as chain links and joints against wear and corrosion.

PROPERTIES

This lubricant assures:

- outstanding lubricating action
- outstandingly adherent
- excellent low temperature behavior
- excellent viscosity/temperature properties

APPLICATIONS

The specifications and instructions from the assembly or equipment manufacturer must be followed.

Meets the requirements of: API SJ

TYPICAL PROPERTIES

Havens Chainsaw Oil 100		
Typical Properties	ISO Grade	100
	Performance	N/A
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.87
Viscosity @ 100°C, cSt	ASTM D445	13
Viscosity @ 40°C, cSt	ASTM D445	100
Viscosity Index	ASTM D2270	128
Flash Point, °C	ASTM D92	220
Pour Point, °C	ASTM D97	-35

August 2020

The values shown above are typical values at the date of publication. Havens Lubricants reserves the right to change these typical values without prior notice