



PRODUCT DATA SHEET

Havens Engine Flush Plus

DESCRIPTION

Havens Engine Flush Plus Engine Flush Plus is a combination of additives and a special carrier fluid. The effective detergent and dispersant additives dissolve sludge. All types of oil-soluble residues are brought into suspension and removed during the next oil change.

APPLICATIONS

Cleaning and flushing out of gasoline and diesel engines. Suitable for vehicles with timing belt running in oil. Not suitable for use on motorbikes with wet clutches.

One 300 ml can is sufficient for up to 6 liters of oil. Add Engine Flush Plus to the motor oil at running temperature before changing the oil. After adding the product, allow the engine to idle for approximately 10 minutes. Then change the oil and the filter. Engine Flush Plus is compatible with all commercially available motor oils.

PROPERTIES

- economical
- does not attack common sealing materials
- rapid cleaning
- suitable with filters and catalytic converters
- minimizes wear
- suitable for turbocharger

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	ENGINE FLUSH PLUS
Color / appearance		-	yellow, brown
Base	-	-	Additives + carrier liquid
Flash point	DIN ISO 2592	°C	60
Pour point	DIN ISO 3016	°C	-30
Form	-	-	liquid
Viscosity at 40 °C	-	-	<7 mm ² /s
Odor	-	-	characteristic

The values shown above are typical values at the date of publication. Havens Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.havenslubricants.com.