



PRODUCT DATA SHEET

Havens Power Steering Fluid

DESCRIPTION

Havens Power Steering Fluid has a sophisticated combination of high quality mineral based oils and viscosity index improve, anti-oxidant, anti-wear, detergent, and friction modifying additives.

APPLICATIONS

Used in automatic transmissions and manual transmissions, in torque converters and numerous power steering systems in accordance with the specifications of the manufacturer.

PROPERTIES

This lubricant assures:

- Smooth transmission and perfect synchronization
- Longer retention of frictional characteristics under continual severe operating conditions
- Protection against deposit formation and evaporation losses at high operating temperatures
- Excellent low temperature operation, ensuring prompt circulation of fluid
- Good protection, against wear, resistance to rust, corrosion and foam
- Compatible with seal materials used in transmission units
- Lower maintenance costs, and improved operating profit

PERFORMANCE LEVEL

Meets and exceeds:

- GM DEXRON II D, Allison C-4, Ford WSS-M2C166-H, MAN Typ Z1/V1, MB 236.1

TYPICAL PROPERTIES

Havens Power Steering Fluid		
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.87
Viscosity @ 100°C, cSt	ASTM D445	8.0
Viscosity @ 40°C, cSt	ASTM D445	40
Viscosity Index	ASTM D2270	175
Flash Point, °C	ASTM D92	200
Pour Point, °C	ASTM D97	-36
Colour	-	Blue

February 2015

The values shown above are typical values at the date of publication. Havens Lubricants reserves the right to change these typical values without prior notice.